

AIR OPERATED GREASE PUMPS

GREASE

AIR OPERATED GREASE PUMPS



Part Number	11148T	11174T	11195T	11348	11374	11395	11748	11848	11595
Pump Ratio	60:1	60:1	60:1	80:1	80:1	80:1	10:1	13:1	35:1
Delivery Rate (oz/min)	48	48	48	126	126	126	70	100	140
Working Pressure PSI	80-120	80-120	80-120	80-120	80-120	80-120	80-145	80-145	80-120
Air Inlet (NPTF)	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Grease Outlet (NPTF)	*1/4"	*1/4"	*1/4"	3/4"	3/4"	3/4"	1"	1 1/4"	3/4"
Air Consumption (cfm)	12	12	12	20	20	20	87	103	20
Noise (dB)	79	79	79	79	79	79	79	79	79
Drum Size (lb)	30/60	120	420	30/60	120	420	N/A	N/A	420
Dia., Suction Tube (in)	1.26	1.26	1.26	1.42	1.42	1.42	2.00	3.00	1.65
Length Suction Tube (in)	19.75	29.50	37.50	19.75	29.50	37.50	N/A	N/A	37.5
Shipping Weight (lb)	12	14	16	20	22	24	32	40	26

Note: For longer pump life and efficiency, we recommend the use of dried air or an air filter. As with any pneumatic equipment, you can expect longer trouble free operation with the use of clean, dry air. The use of an air drier, separator (filter), or minimally an air filter is advantageous. See page 53 for selection of air regulators, separators (filter) and dryers.

* Order with a "-02" suffix (eg; 11174T-02) to receive 3/8" discharge.