

OIL REEL SYSTEM SELECTION GUIDE

The selection guide below allows you to customize the pump/reel/meter system to best fit your application and allows you to take advantage of "system" pricing.

The selection guide steps you through the selection process with the end result being a unique model number detailing your system configuration. Model RS25R25ENQRAFR2 is shown below. It includes a 5:1 stub pump, foot valve, 25 foot hose reel w/ 2 foot jumper hose, electronic meter with quart calibration, rigid spout, auto-tip and a 150 PSI rated filter/regulator with gauge.

Note: Optional items that you may need to complete your system: P/N 540025 Relief Valve Kit, 750 PSI
 P/N 540035 2" Double Tap with 3/8" Return Port
 P/N 22159 2" Bung Spacer with 3/8" Return Port

Note: If you will be plumbing any of these systems with hard, rigid pipe, it is highly recommended to install a relief valve kit, model #540025. When using a stub pump, use relief valve kit #540025 in conjunction with 2" double tap #540035, or bung spacer #22159, for convenient return of "relieved" fluid. See page 25.

SYSTEM IDENTIFIER

RS Oil Transfer System

PUMP SELECTION

- 20 3:1 Stub Pump w/bung adapter
- 21 3:1 Drum Pump to fit 55 Gallon drum, w/bung adapter
- 22 3:1 Pump Kit to fit 275 Gallon Oval Tank, 44" length, w/bung adapter
- 23 5:1 High Flow Stub Pump, 12 GPM
- 24 5:1 High Flow Stub Pump, 8 GPM
- 25 5:1 Stub Pump w/ bung adapter**
- 26 5:1 Drum Pump to fit 55 Gallon drum, w/bung adapter
- 27 5:1 Pump Kit to fit 275 Gallon Oval Tank, 44" length, w/bung adapter

REEL SELECTION

- H20 1/2" x 20' Hose Only
- R25 1/2" x 25' Hose Reel**
- R30 1/2" x 30' Hose Reel
- R40 1/2" x 40' Hose Reel
- R50 1/2" x 50' Hose Reel

METER SELECTION

- VN Control Valve w/o Meter, VN200 Series
- EN Electronic Non-Preset Meter, LD150 Series**
- EB Electronic Non-Preset Meter, LB300 Series
- EP Electronic Preset Meter, K500 Series
- ES Standard Model Electronic Preset Meter, BP100 Series
- MN Mechanical Non-Preset Meter
- MP Mechanical Preset Meter

TYPE OF CALIBRATION

- X Not Applicable
- Q Quart Calibration**
- G Gallon Calibration
- P Pint Calibration

TYPE OF DISCHARGE SPOUT

- R Rigid**
- F Flex
- H Hose, 12"

TYPE OF DISCHARGE TIP

- A Automatic**
- M Manual
- H High Flow Manual

AIR FILTER/REGULATOR/LUBRICATOR W/GAUGE

- xxx No Filter/Regulator
- FR1 FRL Combo, 150 PSI
- FR2 FR COMBO, 150 PSI**
- FR3 FRL COMBO, 230 PSI
- FR4 FR COMBO, 230 PSI

RS25R25ENQRAFR2 shown



RS 25 R25 EN Q R A FR2

Example: Transfer system w/ 5:1 pump, 25' Hose Reel, non-preset electronic meter w/quart calibration, rigid spout, automatic discharge tip and filter regulator combo w/gauge.

NOTE: For pricing see back section of price booklet.

NEW OIL

OIL REEL SYSTEM SELECTION GUIDE