



Accepted

RL Manual Lever Puller

- Standard lift is 5 ft (1.5 m) with additional lifts available.
- High strength, grade 80 alloy steel load chain with galvanized finish for corrosion resistance.
- Steel construction with chrome finish.
- Ideal for construction, maintenance, service and much more.
- 360° handle rotation and rubber grip.
- Hooks are alloy steel, heat treated and equipped with hook latches and inspection points.
- Totally enclosed brake provides protection against dirt.
- Dual pawl Weston-style brake with two friction discs provides four braking surfaces.
- Meets or exceeds international standards, including ASME B30.21.



Model	Capacity Ton [kg]	Falls	Nominal Lever Effort ¹ Lbs. [N]	Handle Length Inch [mm]	Weight ^{**} Lbs. [kg]
RL-250	1/4 [250]	1	55 [245]	6.61 [168]	5 [2.1]

Great little ratchet hoist (500 #s) for small operations: pulling a pipe or beam into place. lifting or moving that heavy part or hauling out the snowmachine or ATV or just to have

¹ Effort required to lift rated load.

^{**} Note: Weights shown are for models with 10 ft. (3m) of lift

Optional belt pouch with detachable shoulder strap makes the RL Lever Puller extremely versatile and portable. Available only for 1/4 ton unit with 5 ft. lift.

