

## QL End Trucks and Bridge Drives

### RSN and RTN (Top Running) Models



- Heavy duty steel construction
- Double flanged wheels
- Rotating axle drive wheel (optional on idler wheel)
- Standard wheels are flat tread ductile iron (approximately 280 BHN)
- Equipped with rail sweeps and bumpers
- Works with GES Bridge Drives
- Bolted girder connection plates

### RU and RH (Under Running) Models

- Two four-wheel articulating trolley design
- Adjustable trolleys to handle various flange widths
- Constructed of structural steel
- Ductile iron, single flange crown tread wheels (approximately 280 BHN)



- Easy access to wheels for maintenance
- Permanently lubricated antifriction bearings
- Equipped with bumpers and drop lugs
- Patented track wheel option
- Works with GEK Bridge Drives

### GEK and GES Bridge Drives



- Fully enclosed gear units are specially designed for crane applications to ensure many years of trouble-free operation
- Modular design includes gearbox, motor and brake for ease of maintenance
- Totally enclosed, 30-minute, Class F insulated motors
- Motor brakes
- Brakes are normally closed. If power fails, brakes will stop further motion.



4501 Gateway Blvd.  
Springfield, OH 45502  
Phone: (937) 328-5100  
Fax: (937) 325-5319  
Nationwide Toll Free:  
1-800-955-9967  
www.rmhoist.com

Bulletin No. QL-2009

LoadMate® is a  
registered trademark of  
R&M Materials Handling, Inc.

R&M Materials Handling,  
Inc. may alter or amend the  
technical specifications  
identified herein at any time  
with or without notice.

© 2009, R&M  
Materials Handling, Inc.

## QL Modular Crane Packages

Innovation . . . Performance . . . Reliability




## QL Modular Crane Packages

Innovation . . . Performance . . . Reliability

### LoadMate® Options

#### Special Low Headroom Trolley Configuration

Using a special trolley frame with an offset hoist, lifting heights can be optimized. This configuration allows for maximum hook height in tight clearance applications.



#### Hoist Control Options

Several control options for the LoadMate® include:

- Variable frequency drive hoist control provides precision hook positioning LM10 frame size only (pictured to the left)
- Tandem control for simultaneous or independent control of two similar hoists on bridge.
- Hour counter for scheduled preventive maintenance as well as hoist SWP (Safe Working Period) calculations

#### QL Crane Options

- Horn
- Radio control
- Flashing light for crane traveling
- Two-speed contactor controls for bridge drives.

Caution: Do not use R&M hoists and trolleys for passenger elevator applications.

R&M Materials Handling, Inc. is a proud member of the following organizations:



YOUR DISTRIBUTOR CONTACT IS:



## QL Modular Crane Packages

QL Modular Crane packages are pre-engineered, complete crane component packages utilizing cutting edge technology including the innovative LoadMate electric chain hoist. Variable frequency drives are standard on trolley and bridge motions for smooth starts and stops. Plug-in electrical cabling\* and bolted structural connections simplify assembly.


- 1/2 to 5 ton capacities with ASME duty ratings; 500 kg - 5,000 kg capacities with FEM duty ratings
- Single girder top running or single girder under running crane configurations
- LoadMate® electric chain hoist with motorized trolley
- Operates with most three phase power supplies (Controls are voltage specific.)
- Two-speed hoist controls, variable frequency trolley and bridge controls are standard
- Standard crane spans up to 62 ft. [19m] Longer spans available.
- Pendant controller or optional RaCon II radio controller
- Pre-engineered crane electrification package
- Various crane options and hoist options are available
- Indoor service



Plug-in pendant connection



Standard bolted girder connection plates



Optional RaCon® II Radio Control

PB Pendant Configurations



Plug-in festoon connections

### QL Bridge Controls standard features:

- Standard inverter offers two speed or infinitely variable speed control
- CSA c/us approved NEMA 4/IP55 type rated control enclosures for indoor use
- Mainline disconnect switch (mounted in door)
- Mainline contactor
- Plug-in connections for easy assembly and maintenance\*
- Control transformer with fused secondary
- Supports 208, 230, 460 or 575/3/60 power supply - 115 volt control voltage is standard (48 volt is optional)
- Supports 380/3/50 power supply - 48 volt control voltage is standard
- Slow down bridge traveling limit switch

Proprietary QuoteMaster® software configures a crane package offer in seconds.



Galvanized steel cable trolleys

### Crane Electrification Package Festoon System

- PVC flat cables are UL listed and CSA approved with a temperature range of -31°F to +221°F (-35°C to +105°C)
- Suspended from galvanized steel C-track
- Galvanized steel cable trolleys with steel and plastic cable supports
- Plug connections\* on cables make installation, repair and replacement simple and fast, saving expensive down time and the cost of an electrician
- All movements can be controlled from a convenient, easy-to-reach plug-in pushbutton station (8 buttons including emergency stop button)
- Independent C-track for pendant station allows operator to be positioned at a safe distance from load

\* Plug-in connections may not be available for packages with spans over 62 ft [19 m] or 208 or 230/3/60 power supply.

LoadMate® hoists are designed to maximize productivity with fast installation, easy operation and built-in durability. The compact design provides low headroom and allows close trolley approaches. R&M's advanced design and manufacturing techniques ensure safe operation, consistent quality and longer component life. It adds up to exceptional value - hoist equipment that saves on maintenance, repair and downtime costs over its lifetime.

### Flexibility to meet your exact requirements

R&M LoadMate® electric chain hoists offer a range of choices for a wide variety of applications.

- 1/2 to 5 ton capacities with ASME duty ratings; 500 kg - 5,000 kg with FEM duty ratings
- 10, 15 and 20 ft. [3 -6 m] lifts standard; additional lifting heights available up to 150 ft. [46m] single fall, 75 ft. [23 m] two fall.
- Two speed, three phase hoist motors and controls. Lift speeds from 12/3 fpm [3.6/0.9 m/min] to 32/8 fpm [9.8/2.5 m/min] (speeds reached with 60Hz power supply).
- Hoist motors are class F insulated, 50% effective duty rated.
- TMU trolley drive unit with inverter controls. Standard trolley inverter offers two-speed or infinitely variable speed control.
- Trolley control panel integrally mounted to the motor.
- Trolley brake, bumpers and drop lugs are standard.

### REDUCED MAINTENANCE Quality keeps your hoist on the job long past the pay-off point

LoadMate® hoists are designed to run cool and maximize the life of gears, brakes and motors. Longer component life means less maintenance, less downtime and lower repair costs.

- Sealed brake keeps out lubricants.
- The hoist brake and load limiter are both adjustable and adjust independently of each other.

### EASE OF OPERATION Innovative design enhances versatility and ease of use

- Premium-grade, AGMA rated\* precision gearing contributes to the hoist's compact, low-headroom design, low noise level and smooth operation.
- Integral hoist control panel encloses all electrical components (hoist contactors, transformer, terminal strips, etc.) and is easily accessed for maintenance.



- Easy trolley mounting attachment meets various application requirements. Slot in top of hoist body allows easy changeover of top hook, push trolley or motorized trolley mountings.
- Crown tread wheels standard on trolleys, for use on standard I-beams and wide flange beams.

\* Hoist gearboxes: LM1: AGMA 10, LM05 & LM10: AGMA11 and LM16/25: AGMA 12. Traveling gearboxes: AGMA 10.

For the most current technical guides, drawings and other product information visit our website at

[www.rmhoist.com](http://www.rmhoist.com)