

December 7, 2006 2006

P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current as of Dec. 7, 2006

SYNTHETIC AIR COMPRESSOR

ULTIMA

Summit Ultima is a high performance lubricant formulated specifically to outperform other synthetic rotary compressor lubricants on the market. Ultima employs a unique base stock that allows improvements in oxidation resistance and sludge and deposit formation over conventional synthetic base stocks. It is also compatible with existing O.E.M. provided lubricants. Please contact your Summit representative for additional information.

Physical Properties

PRODUCTS	Ultima	Ultima 68
ISO Grade	46	68
Viscosity		
@ 40°C, cSt	50	63.2
@ 100°C, cSt	7.35	9.28
@ 100°F, SUS	257	325
@ 210°F, SUS	50.9	57.5
Viscosity Index	108	126
Specific Gravity	0.921	0.920
Tan	0.28	0.28
Flash Point, °F (°C)	490 (254)	490 (254)
Pour Point, °F (°C)	-49 (-45)	-49 (-45)
RPVOT, Avg. Minutes	3600	3600
Rust	Pass	Pass
Emulsion Tendency	40/40/0 (20 mins.)	40/40/0 (20 mins.)